

WASH PRIMER WHITE

Code R10.96.920.0

PRODUCT DESCRIPTION

Products based on polyvinyl phenolic resins modified with outstanding adhesion power on metal surfaces, particularly on light alloys.

Compared to ordinary wash primer, it offers the features of a good filling properties.

APPLICATION FIELDS

As a protective layer or fixing primer for further applications of paints or enamels in a wide range of industrial sectors.

It can be applied directly on steel, cast iron, aluminum, zinc and alloys.

Because of the good appearance of the film, it may also be employed as a matt finish too.

It offers outstanding performances in the lighting industry, for aluminum substrates.

PRODUCT SPECIFICATIONS


Dry content of component A	32,5 ± 2 %	(Internal system)
Viscosity Cup F4 at 20° C	100"± 2"	(4 DIN 53211)
Specific weight	1030 1050 gr / lt	(UNI 8910)
Theoretical coverage	8-10 mq / kg	
Recommended thickness	15 / 20 micron per layer	
Film appearance	matt	
Impact resistance	Excellent	(UNI 8901)
Adhesion (cross-cut test)	classification 0	(UNI 2409)

(The edges of the cuts are perfectly undamaged: no small square came off)



SUBSTRATE PREPARATION

Clean and degrease the substrates before applying the primer.

APPLICATION PROCESS

	Conventional spray	THINNER 70.08.324.0	Vix of application CF4 at 20° C
		70-100% In weight	17" / 20"

DRYING

Air		Dust free	5' – 10'	20° C
		Tack free	20' – 25'	20° C
		Through drying	6 / 8 h	20° C
Oven			20' / 30'	80 / 70° C

NOTES

This is a solvent based product.

If its use takes place in a closed environment, it is recommended to guarantee a good ventilation and use a protective masks.

Storage of the product must occur in locations with equipment up to standard, however, far away from heat sources and open flames

For any further information, please refer to the appropriate safety data sheet.

IMPORTANT NOTE: The information in this sheet are not intended to be exhaustive and is based on our current knowledge and on current laws: anyone who uses the product for purposes other than those specifically recommended in the data sheet without first obtaining written permission, does it at his/her own risk. This information is given only as a guide and cannot engage the responsibility of our company nor provide a pretext for disputes of any kind that might still be associated with the use of the described products. Any suggestions or statements made by us regarding the product (in this sheet and in other ways) are correct to the best of our knowledge, however, are beyond our control the quality or state of the substrate or the many external factors affecting the use or application of the product. Consequently, in the absence of a specific written agreement, we accept no liability for product performance or for any loss or damage caused by it. All products and the technical advices provided are subject to our standard terms and conditions of sale. The information contained in this form are subject to periodic changes in the light of experience and our policy of continuous development. It is user's responsibility to check that this sheet is current prior to using the product.

EPTACOAT