

Thinner for Solvent Based Inks

Code A31890900

PRODUCT DESCRIPTION

These thinners are compatible with solvent based inks.

APPLICATION FIELDS

These thinners may be used when it is necessary to reduce viscosity of solvent based inks, before printing.

APPLICATION PROCESS

Inks	HI-GLOSS	serie A31135000
	CARBOGLOSS	serie A31126000
	VINILFAST	serie A31136000
	VINILFLAT	serie A31138000
	VINYL-GLO	serie A31172000
	METALINK	serie A31194000
	THERMOPLUS	serie A31149000
	ACRILUX	serie A31148000
	CELLOFLEX	serie A31120000
	TEXYLON	serie A31158000
	VINILPOSTER	serie A31124000
	ONDAFLUTE	serie A31185000
	EPOXSER	serie A31192000
SERIPOXY	serie A31190000	
Effetti speciali		
Quantity	According to the type of ink used and the printing requirements	
Thinners	See the product range table	
Storage	Away from direct sunlight and heat sources	
Package	See the product range table	
Safety Data Sheet	Available upon request	

GENERAL FEATURES

- Very wide product range
- Wide application field
- Compatible with all the solvent based inks
- Excellent solvent power
- Ideal to lower the viscosity

PREPARATION

Pour the selected thinner into the ink to be used, and mix well, before printing.

TECHNICAL FEATURES

The products range from very quick to extremely low thinners.

The thinner quantity to be added is in accordance with its evaporation and the available printing technology.

SPECIAL INSTRUCTIONS

- Always test the characteristics of the product, before starting production.
- The above information is the result of previous knowledge and experience; it is neither a guarantee nor an assurance.
- Choose the most indicated thinner, according to the ink.
- Choose the thinner also according to the substrate to be printed.

PRODUCT RANGE

CODE	PRODUCT	EVAPORATION	PACKAGE	Compatibility with solvent based inks													Notes	
				HIGLOSS	CARBOGLOSS	VINILFAST	VINILFLAT	THERMOPLUS	VYNIL-GLO	METALINK	ACRILUX	CELLOFLEX	TWXYLON	POSTERFAST	VINILPOSTER	ONDAFLUTE		SERIPOXY
A3189092100-	DILUENTE 90.921 SPRUZZO ODOROSO	Very quick	1 l and 5 l	X	X	X	X	X	X	X		X		X		X	X	
A3189090400-	DILUENTE 90.904 RAPIDO	Quick	1 l and 5 l	X	X	X	X	X	X	X		X	X	X	X	X	X	X
A3189092500-	DILUENTE 90.925 RAPIDO INODORE	Quick	1 l and 5 l										X		X			
A3189092700-	DILUENTE 90.927 NORMALE ODOROSO	Middle	1 l and 5 l	X	X	X	X		X	X			X					Contains PAHs*
A3189091300-	DILUENTE 90.913 NORMALE INODORE	Middle	1 l and 5 l	X	X	X	X	X	X	X	X	X		X				
A3189091700-	DILUENTE 90.917 NORMALE INODORE	Middle	1 l and 5 l	X	X	X	X	X	X	X				X		X		Contains PAHs*
A3189092200-	DILUENTE 90.922 NORMALE	Middle	1 l and 5 l														X	X
A3189092400-	DILUENTE 90.924	Middle	1 l and 5 l	X		X	X	X	X	X	X	X	X	X	X	X		
A3189099200-	DILUENTE 90.992 MEDIO	Middle	1 l and 5 l	X	X	X	X	X	X	X	X						X	X
A3189091800-	DILUENTE 90.918 LENTO	Slow	1 l and 5 l	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
A31890911NF00-	DILUENTE 90- 911NF EXTRA LENTO	Very slow	1 l and 5 l	X	X	X	X	X	X	X		X	X		X		X	X
A3189093100-	DILUENTE 90.931 EXTRA LENTO INODORE	Very slow	1 l and 5 l														X	X
A31890923001	DILUENTE 90.923 RITARDANTE INODORE	Very slow	1 l	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
A3189099800-	RITARDANTE 90.998	Very slow	1 l and 5 l														X	X

* acronym for Polycyclic Aromatic Hydrocarbon



IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.